

ASUS PRIME B560M-K - motherboard - micro ATX - LGA1200

Socket - B560



23-05-2024

SKU	90MB1650-M0EAY0
Produktbeskrivelse:	ASUS PRIME B560M-K - bundkort - micro-ATX - LGA1200 sokkel - B560
Produkttype:	Bundkort - micro-ATX
Chipsættype:	Intel B560
Processor-socket:	1 x LGA1200 sokkel
Kompatible processorer:	(understøtter 11. Generation Intel Core og 10. Generation Intel Core / Pentium Gold / Celeron)
Max RAM-størrelse:	128 GB
RAM understøttet:	2 DIMM slots - DDR4, ikke-ECC, ikke bufferet

Generelt

Produkttype:	Bundkort - micro-ATX
Chipsættype:	Intel B560
Processor-socket:	LGA1200 sokkel
Max antal processorer:	1
Kompatible processorer:	(understøtter 11. Generation Intel Core og 10. Generation Intel Core / Pentium Gold / Celeron)

Diverse

Udstyr inkluderet:	I/O- bagvæg, 2 x M.2 ankre
Medfølgende ledninger:	2 x Serial ATA kabel
Med software:	Drivers & Utilities, ASUS AI Charger, ASUS CPU-Z, ASUS AI Suite III, ASUS EZ Update, ASUS EZ Flash 3, DAEMON Tools, WinRAR, Norton AntiVirus (Trial)
Bredde:	24.4 cm
Dybde:	21.1 cm

Understøttet RAM

Maks. størrelse:	128 GB
Teknologi:	DDR4
Bus Clock:	2400 MHz, 2133 MHz, 2800 MHz, 2666 MHz, 2933 MHz, 3400 MHz (O.C.), 3333 MHz (O.C.), 3733 MHz (O.C.), 3600 MHz (O.C.), 4000 MHz (O.C.), 4400 MHz (O.C.), 4266 MHz (O.C.), 4600 MHz (O.C.), 4800 MHz (O.C.), 3200 MHz, 5000 MHz (O.C.)
Understøttet RAM-integritetskon:	Ikke-ECC
Registreret eller buffer:	Ikke bufferet

Egenskaber

BIOS-type (Basic Input/Output System):	AMI
BIOS-egenskaber:	UEFI BIOS
Sov/ Vågn:	Aktivering af LAN (wake on LAN = WOL), vågn på PME

Understøttet RAM

Egenskaber:	Dobbelt kanal hukommelses arkitektur, Intel Extreme Memory Profiles (XMP)
-------------	---

Audio

Type:	HD Audio (8-kanaler)
Audio codec:	Realtek ALC897
Overensstemmelsesstandarder:	High Definition Audio

LAN

Netværk controller:	Intel I219V
Netværks interfaces:	Gigabit Ethernet

Egenskaber

Hardware egenskaber:	Jack retasking, ASUS Q-Design, Q-DIMM, ASUS EZ DIY, Q-Slot, CrashFree BIOS 3, audio jack detektions teknologi, ASUS Fan Xpert, Intel Turbo Boost Technology 2.0, ASUS DIGI+ VRM, ASUS Enhanced DRAM Overcurrent Protection, Preboot eXecution Environment (PXE), ASUS Stainless Steel Back I/O, LANGuard, ASUS Overvoltage Protection, Lighting Control, ASUS 5X Protection III, ASUS SafeSlot Core, Intel Turbo Boost Max Technology 3.0
----------------------	---

Ekspansion / Konnektivitet

Ekspansionsåbninger:	1 x CPU ; 2 x DIMM 288-pins ; 1 x PCIe 4.0 x16 (PCIe 4.0 x16 tilstand (11. Gen Intel CPUer); PCIe 3.0 x16 tilstand (10. Gen Intel CPUer)) ; 2 x PCIe 3.0 x1
----------------------	---

Grænseflade (lagring):	SATA-600 -stikforbindelser: 6 x 7-pin Serial ATA ; SATA-600 / PCIe 3.0 -stikforbindelser: 1 x M.2 ; PCIe 4.0 -stikforbindelser: 1 x M.2
------------------------	---

Interface:	1 x LAN (Gigabit Ethernet) ; 1 x audio linje-ind - mini-jack ; 1 x audio linje-ud - mini-jack ; 1 x mikrofon - mini-jack ; 4 x USB 3.2 Gen 1 ; 1 x PS/2-tastatur/mus ; 1 x VGA ; 1 x HDMI ; 2 x USB 2.0
------------	---

Interne interfaces:	4 x USB 2.0 - intern stik ; 1 x højttaler - intern stik ; 2 x USB 3.2 Gen 1 - intern stik ; 1 x audio - intern stik ; 1 x seriel - intern stik ; 1 x SPDIF ud - intern stik
---------------------	---

Strømkontakter:	24-pin hovedstrøm-konnektor, 8-pin ATX12V-kontakt
-----------------	---

