

ASUS WS C621E SAGE (BMC) - motherboard - SSI EEB - Socket P - C621



Ikke på lager

SKU	90SW0021-M0EAY0
Produktbeskrivelse:	ASUS WS C621E SAGE (BMC) - bundkort - SSI EEB - Socket P - C621
Produkttype:	Bundkort - SSI EEB
Chipsættype:	Intel C621
Processor-socket:	2 x Socket P
Kompatible processorer:	Xeon (Maksimal TDP 205 watt)
Max RAM-størrelse:	768 GB
RAM understøttet:	12 DIMM åbninger - DDR4, ECC, registreret, Load-Reduced, 3DS Load-Reduced, 3DS-registreret

Generelt

Produkttype:	Bundkort - SSI EEB
Chipsættype:	Intel C621
Processor-socket:	Socket P
Max antal processorer:	2
Kompatible processorer:	Xeon (Maksimal TDP 205 watt)

Understøttet RAM

Maks. størrelse:	768 GB
Teknologi:	DDR4
Bus Clock:	2400 MHz, 2666 MHz
Understøttet RAM-integritetskon:	ECC
Registreret eller buffer:	Registreret, Load-Reduced, 3DS Load-Reduced, 3DS-registreret

Grafik

Grafik controller:	ASPEED AST2500
Dedikeret videohukommelse:	64 MB

Audio

Type:	HD Audio (8-kanaler)
-------	----------------------

Diverse

Bredde:	30.5 cm
Dybde:	33 cm

Egenskaber

BIOS-egenskaber:	USB BIOS Flashback
Hardware egenskaber:	Jack retasking, ASUS Q-Design, Q-DIMM, audio jack detektions teknologi, ASUS Q-Shield, ASUS DIGI+ VRM, NVIDIA 4-way SLI Technology Support, Q-Code, ASUS 2 Phase DRAM Power Design, 7+1 Phase Power Design, AMD 4-vejs CrossFireX teknologisupport, anti-popfunktion, ProCool Power Connector, ASUS Gamer's Guardian, ASUS SafeSlot, BMC-fjernadministration

Ekspansion / Konnektivitet

Ekspansionsåbninger:	2 x CPU 12 x DIMM 288-pins 3 x PCIe 3.0 x16 2 x PCIe 3.0 x16 (dual x8 mode; single kort: x16 mode) 2 x PCIe 3.0 x16 (x8-modus)
----------------------	--

Audio

Audio codec:	Realtek ALC51220A
Overensstemmelsesstandarder:	DTS Connect, High Definition Audio, DTS Headphone:X

LAN

Netværk controller:	Intel I210-AT
Netværks interfaces:	2 x Gigabit Ethernet

Ekspansion / Konnektivitet

Grænseflade (lagring):	Intel C621: SATA-600 - stikforbindelser: 8 x 7-pin Serial ATA - RAID 0 / RAID 1 / RAID 10 / RAID 5 SATA-600 - stikforbindelser: 2 x 7-pin Serial ATA PCIe 3.0 -stikforbindelser: 4 x U.2 SATA-600 / PCIe 3.0 - stikforbindelser: 1 x M.2
Interface:	2 x LAN (Gigabit Ethernet) 1 x TOSLINK 1 x USB 3.1 Gen 2 1 x USB-C Gen2 4 x USB 3.1 Gen 1 1 x mikrofon - mini-jack 1 x audio linje-ind - mini-jack 1 x audio linje-ud - mini-jack 1 x audio linje-ud (centrum/subwoofer) - mini-jack 1 x audio linje-ud (bagtil) - mini-jack 2 x USB 2.0 1 x PS/2-tastatur/mus
Interne interfaces:	2 x USB 2.0 - intern stik 4 x USB 3.1 Gen 1 - intern stik 1 x VGA - intern stik 1 x audio - intern stik 1 x seriel - intern stik
Strømkontakter:	24-pin hovedstrøm-konnektor, 2 x 8-pins ATX12V stikforbindelser

