

Cisco Integrated Services Router 1121 - router - desktop



Ikke på lager

SKU	C1121-8PLTEPWE
Produktbeskrivelse:	Cisco Integrated Services Router 1121 - router - desktop
Enhedstype:	Router - 8-port switch (integreret)
Pakningstype:	Desktop
Mobilprotokol:	LTE
Antal WAN porte:	2
Dataforbindelsesprotokol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Netværks/overføselsprotokol:	IPSec, PPPoE, DHCP, DNS, L2TPv3

Generelt

Enhedstype:	Router - 8-port switch (integreret)
Pakningstype:	Desktop
Forbindelsesteknologi:	Trådløs, kabling
Dataforbindelsesprotokol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Netværks/overføselsprotokol:	IPSec, PPPoE, DHCP, DNS, L2TPv3
Routingprotokol:	OSPF, IS-IS, RIP-1, RIP-2, BGP, EIGRP, HSRP, DVMRP, VRRP, PIM-SM, statisk IP routing, IGMPv3, GRE, PIM-SSM, police-baseret routing (PBR), MPLS, Bidirectional Forwarding Detection (BFD), RSVP
Protokol til fjernadministration:	SNMP, RMON, CLI, TR-069
Krypterings algoritme:	DES, trippel DES, SHA, MD5, IKE, ECDSA, 128-bit AES, 256-bit AES, 1024-bit RSA, 2048-bit RSA, 256-bit SHA, 512-bit SHA, 748-bit RSA, 384-bit SHA
Autentificeringsmetode:	RADIUS

Miljømæssige parametre

Min. driftstemperatur:	0 °C
Maks. driftstemperatur:	40 °C
Fugtighedsgrad ved brug:	5 - 95 % (ikke-kondenserende)

Effekt

Strømenhed:	Ekstern strømforsyning
Nødvendig spænding:	AC 120/230 V (50/60 Hz)

Ekspansion / Konnektivitet

Interface:	WAN: 1 x 1000Base-T/1000Base-X - RJ-45/SFP ; LAN: 4 x 1000Base-T - RJ-45 ; LAN: 2 x 1000Base-T (PoE) - RJ-45 ; LAN: 2 x 1000Base-T (PoE+) - RJ-45 ; USB 3.0: 1 x konsol
------------	---

Kommunikationer

Mobilprotokol:	LTE
----------------	-----

Generelt

Egenskaber:

CBWFQ, WRED, ACL support, QoS, DMVPN, NetFlow, MRC, IPFIX, CSD, LISP, pakkesammenlægning A-MPDU, pakkesammenlægning A-MSDU, MIB II, AVC, AAA, DFS, ERSPAN, EEM

Overensstemmelsesstandarder:

IEEE 802.3af, IEEE 802.11i, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3at, IEEE 802.11r, CISPR 24, EN 61000-3-2, EN55022, ICES-003, EN 61000-3-3, EN55024, CISPR 22, CB, EN 61000-6-1, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EN 61000-4-5, EN 61000-4-11, FCC CFR47 Part 15, UL 60950-1 Second Edition, VCCI V-3, EN 60950-1 Second Edition, IEC 60950-1 Second Edition, AS/NZS CISPR 22, CNS 13438, EN 301 489-7, EN 301 489-1, FCC CFR47 Part 22, FCC CFR47 Part 24, CAN/CSA C22.2 No. 60950-1 Second Edition, EN 300 386, EN 301 489-24, EN 301 908-1, EN 301 908-2, EN 301 511, EN 301 908-13

RAM:	4 GB
Flashhukommelse:	4 GB
Statusindikatorer:	Status