

Intel Next Unit of Computing 13 Pro Board - NUC13ANBi3 - motherboard - UCFF - Intel Core i3 i3-1315U



06-06-2024

SKU	BNUC13ANBI30000
Produktbeskrivelse:	Intel Next Unit of Computing 13 Pro Board - NUC13ANBi3 - bundkort - UCFF - Intel Core i3 i3-1315U
Produkttype:	Bundkort - UCFF
Processor:	Intel Core i3 i3-1315U (6 kerner)
Processor-socket:	1
Max RAM-størrelse:	64 GB
RAM understøttet:	2 SO DIMM-åbninger - DDR4, ikke-ECC
Lagringsporte:	1 x SATA-600, 2 x M.2

Generelt

Produkttype:	Bundkort - UCFF
Processor:	Intel Core i3 i3-1315U (6 kerner)
Cachehukommelse:	Intel Smart Cache - 10 MB
Max antal processorer:	1

Understøttet RAM

Maks. størrelse:	64 GB
Teknologi:	DDR4
Bus Clock:	3200 MHz
Understøttet RAM-integritetskon:	Ikke-ECC

Egenskaber:	Dobbelt kanal hukommelses arkitektur
-------------	--------------------------------------

Grafik

Grafik controller:	Intel UHD Graphics
--------------------	--------------------

LAN

Netværk controller:	Intel I226-V
Netværks interfaces:	2.5 Gigabit Ethernet

Ekspansion / Konnektivitet

Oplysninger om kompatibilitet

Designet for:	Intel Next Unit of Computing 13 Pro Kit - NUC13ANHi3, 13 Pro Kit - NUC13ANKi3
---------------	---

Producentgaranti

Service & Support:	Begrænset garanti - 3 år
--------------------	--------------------------

Miljømæssige standarder

ENERGY STAR-certificeret:	Ja
---------------------------	----

Diverse

Ekspansion / Konnektivitet

2 x SO-DIMM 260-pins (1.2 V) (DDR4) ; 1 x M.2 socket (2280 M.2 Key M-åbning) ; 1 x M.2 socket (2242 M.2 Key B-åbning) ; 1 x M.2 socket (2230 M.2 Key E-åbning)

Grænseflade (lagring): SATA-600 -stikforbindelser: 1

Interface: 2 x Thunderbolt 4/DisplayPort/USB4 ; 3 x USB 3.2 Gen 2 ; 1 x USB 2.0 ; 2 x HDMI ; 1 x LAN (2.5Gigabit Ethernet) ; 1 x hovedtelefoner/mikrofon - mini-jack

Interne interfaces: 2 x USB 2.0 - intern stik ; 1 x USB 3.2 Gen 2 ; Seriel - intern stik

Strømkontakter: DC-i strøm stikforbindelse

Diverse

Overensstemmelsesstandarder:

ICES-003, EN55024, FCC Part 15 B, FCC Part 15 C, IEC 60950-1, EN 60950-1, AS/NZS 4268, FCC Part 15 E, BSMI CNS 13438, CISPR, REACH, E-Standby, CEC, ERP, CEL, EN 62311, EN 300.440, China RoHS, EN 300 328, GEMS, EN 301 489-1, KN32, KN35, EN 62368-1, IEC 62368-1, AS/NZS 2772.2, EN 301 893, EN 55032, EN 301 489-3, EU RoHS, UL 62368-1, EN 301 489-17, ARPANSA, Taiwan BSMI RoHS, AS/NZS CISPR 32, VCCI 32

Bredde:	10.4 cm
Dybde:	10.2 cm

