

Lenovo ThinkSystem Broadcom 5719 - network adapter - OCP - Gigabit Ethernet x 4



På lager(8)

SKU	4XC7A08235
Produktbeskrivelse:	Lenovo ThinkSystem Broadcom 5719 - netværksadapter - OCP - Gigabit Ethernet x 4
Enhedstype:	Netværksadapter
Grænseflade (bus) type:	Open Compute Project mezzanine (OCP)
Porte:	Gigabit Ethernet x 4
Dimensioner (B x D x H):	11.5 cm x 7.6 cm
Kabeltype:	Ethernet 10Base-T, Ethernet 100Base-TX, Ethernet 1000Base-T
Dataforbindelsesprotokol:	10Mb LAN, 100Mb LAN, 1GbE

Generelt

Enhedstype:	Netværksadapter
Grænseflade (bus) type:	Open Compute Project mezzanine (OCP)

Netværk

Porte:	Gigabit Ethernet x 4
Forbindelsesteknologi:	Kabling
Kabeltype:	Ethernet 10Base-T, Ethernet 100Base-TX, Ethernet 1000Base-T
Dataforbindelsesprotokol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Dataoverførselshastighed:	1 Gbps
Netværks/overførselsprotokol:	TCP/IP
Egenskaber:	WOL, Jumbo Frames-support (op til 9600 byte)
Overensstemmelsesstandarder:	IEEE 802.3z, IEEE 802.1Q, IEEE 802.3x, IEEE 802.1ad, IEEE 802.3az

Processor / Hukommelse

Processor:	1 x Broadcom BCM5719
------------	----------------------

Oplysninger om kompatibilitet

Designet for:	Lenovo ThinkAgile VX2330 Appliance 7Z62 ; Lenovo ThinkAgile VX3330 Appliance 7Z62 ; Lenovo ThinkAgile VX3331 7Z62 ; Lenovo ThinkAgile VX3530-G Appliance 7Z63 ; Lenovo ThinkAgile VX3575-G Integrated System 7D43 ; Lenovo ThinkAgile VX5530 Appliance 7Z63 ; Lenovo ThinkAgile VX5575 Integrated System 7D43 ; Lenovo ThinkAgile VX7330-N Appliance 7Z62 ; Lenovo ThinkAgile VX7530 Appliance 7Z63 ; Lenovo ThinkAgile VX7531 Certified Node 7Z63 ; Lenovo ThinkAgile VX7575 Integrated System 7D43 ; Lenovo ThinkAgile VX7576 Certified Node 7D43 ; Lenovo ThinkSystem SR630 V2 7Z71 ; Lenovo ThinkSystem SR635 7Y99 ; Lenovo ThinkSystem SR645 7D2X ; Lenovo ThinkSystem SR650 V2 7D15, 7Z73 ; Lenovo ThinkSystem SR655 7Z01 ; Lenovo ThinkSystem SR665 7D2V, 7D2W ; Lenovo ThinkSystem SR670 V2 7Z23 ; Lenovo ThinkSystem SR850 V2 7D32
---------------	--

Miljømæssige parametre

Min. driftstemperatur:	10 °C
Maks. driftstemperatur:	35 °C
Fugtighedsgrad ved brug:	20 - 80 % (ikke-kondenserende)

Ekspansion / Konnektivitet

Interface: 4 x 1000Base-T - RJ-45

Producentgaranti

Service & Support: Begrænset garanti - 1 år

Mål og vægt

Dybde: 11.5 cm

Højde: 7.6 cm

Diverse

Overensstemmelsesstandarder: VCCI, BSMI, EN 60950, EN 61000-3-2, EN55022, RRL, UL 1950, EN 61000-3-3, EN55024, RoHS, AS/NZS CISPR 22, ICES-003 issue 4, FCC CFR47 Part 15 A, IEC 950, CSA C22.2 950-95, IEEE 802.1Q

