

StarTech.com USB C Multiport Adapter, Mini USB-C Dock with Single Monitor VGA 1080p Video, 60W Power Delivery Passthrough, USB 3.1 Gen 1 Type-A 5Gbps, Gigabit Ethernet, Docking Station - Portable USB C Dock (DKT30CVAGPD) - docking station - USB-C - VGA -



Ikke på lager

SKU	DKT30CVAGPD
Produktbeskrivelse:	StarTech.com USB C Multiport Adapter, Mini USB-C Dock with Single Monitor VGA 1080p Video, 60W Power Delivery Passthrough, USB 3.1 Gen 1 Type-A 5Gbps, Gigabit Ethernet, Docking Station - Portable USB C Dock (DKT30CVAGPD) - dockingstation - USB-C - VGA - 1GbE
Produkttype:	Dockingstation
Docking-interface:	USB-C
Videointerfacer:	VGA
Dimensioner (B x D x H):	4 cm x 9.6 cm x 1.65 cm
Vægt:	46.9 g
Farve:	Sort



Generelt

Produkttype:	Dockingstation
Bredde:	4 cm
Dybde:	9.6 cm
Højde:	1.65 cm
Vægt:	46.9 g
Fås i farverne:	Sort

Video

Maks. opløsningdetaljer:	1920 x 1200 - 60 Hz
--------------------------	---------------------

Netværk

Dataforbindelsesprotokol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Overensstemmelsesstandarder:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

Ekspansion / Konnektivitet

Interface:	1 x netværk - 1000Base-T - RJ-45 1 x SuperSpeed USB 3.0 with Fast Charging - 9 pin USB Type A 1 x USB-C med Power Delivery - 24 pin USB-C (kun strøm) 1 x video - VGA - 15 pin HD D-Sub (HD-15)
------------	---

Miljømæssige parametre

Min. driftstemperatur:	0 °C
Maks. driftstemperatur:	45 °C

Mål & vægt (forsendelse)

Vægt ved forsendelse:	60 g
-----------------------	------

Producentgaranti

Service & Support:	Begrænset garanti - 3 år
--------------------	--------------------------

Systemkrav

OS nødvendig:	Google Chrome OS 55 eller senere, Apple MacOS X 10.11 - 10.15, Apple macOS 11.0, Microsoft Windows 7 / 8 / 8.1 / 10 / 11, Apple macOS 12.0, Apple macOS 13.0
---------------	--

Diverse

Medfølgende ledninger:	1 x USB-C kabel - integreret - 14.3 m
Egenskaber:	Strøm fra USB, fuld duplex-support, 60 W strømlevering
Overensstemmelsesstandarder:	FCC, RoHS, USB Battery Charging Specification Rev. 1.2, USB Power Delivery 2.0, UASP (USB Attached SCSI Protocol)

