

StarTech.com USB-C & USB-A Dock, Hybrid Universal Laptop Docking Station with 100W Power Delivery, Dual Monitor 4K 60Hz HDMI & DisplayPort, 4x USB 3.1 Gen 1 Hub, Gigabit Ethernet (GbE) - Hybrid USB Type-C Dock (DK30C2DPEPUE) - docking station - USB-C - 2



På lager(16)

SKU	DK30C2DPEPUE
Produktbeskrivelse:	StarTech.com USB-C & USB-A Dock, Hybrid Universal Laptop Docking Station with 100W Power Delivery, Dual Monitor 4K 60Hz HDMI & DisplayPort, 4x USB 3.1 Gen 1 Hub, Gigabit Ethernet (GbE) - Hybrid USB Type-C Dock (DK30C2DPEPUE) - dockingstation - USB-C - 2 x HDMI, 2 x DP - 1GbE
Produkttype:	Dockingstation
Docking-interface:	USB-C
Videointerfacer:	2 x HDMI, 2 x DP
Dimensioner (B x D x H):	22 cm x 8 cm x 3 cm
Vægt:	280 g
Farve:	Sort, space grey



Generelt

Produkttype:	Dockingstation
Bredde:	22 cm
Dybde:	8 cm
Højde:	3 cm
Vægt:	280 g
Fås i farverne:	Sort, space grey
Lokalisering:	United Kingdom, Europa

Video

Maks. opløsningdetaljer:	4096 x 2160 - 60 Hz
--------------------------	---------------------

Netværk

Dataforbindelsesprotokol:	Ethernet, Fast Ethernet, Gigabit Ethernet
Overensstemmelsesstandarder:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, USB 1.1, USB 2.0, USB 3.0

Ekspansion / Konnektivitet

Interface:	1 x USB 3.1 Gen 1 with Power Delivery - 9 pin USB Type A 2 x USB 3.1 Gen 1 with Power Delivery - 24 pin USB-C 2 x skærm/video - 20 pin DisplayPort 2 x skærm/video - 19 pin HDMI Type A 1 x netværk - 10Base-T/100Base-TX/1000Base-T - RJ-45 1 x USB 3.1 Gen 1 - 9 pin USB Type A 1 x hovedtelefon/mikrofon-kombistik - minitelefons 3,5 mm
------------	---

Miljømæssige parametre

Min. driftstemperatur:	0 °C
Maks. driftstemperatur:	50 °C

Producentgaranti

Service & Support:	Begrænset garanti - 3 år
--------------------	--------------------------

Systemkrav

OS nødvendig:	Apple macOS 10.12, Google Chrome OS 55 eller senere, Ubuntu 18.04, Apple macOS 10.14, Apple macOS 10.11, Apple macOS 10.15, Ubuntu 20.04, Apple macOS 11.0, Microsoft Windows 7 / 8 / 8.1 / 10 / 11, Apple macOS 12.0, Apple macOS 13.0
---------------	---

Effekt

Strømenhed:	Strømforsyningsadapter
Nødvendig spænding:	AC 120/230 V
Strømforsyning:	170 Watt

Diverse

Medfølgende ledninger:	1 x USB-C kabel - eksternt - 1 m
Egenskaber:	Slot sikkerhedslås (kabel lås sælges separat), arm til to monitorer, Preboot Execution Environment (PXE) support, fuld duplex-support, DisplayPort Alt Mode, 100 W strømlevering
Sikkerhedsåbningstype:	Kensington-sikkerhedsåbning
Overensstemmelsesstandarder:	FCC, RoHS, USB Battery Charging Specification Rev. 1.2, DisplayPort 1.2, UASP (USB Attached SCSI Protocol), USB Power Delivery 3.0

